



COVE-MATE

Coving and Decorating Adhesive

Description

A high strength, solvent-free, gap-filling coving and decorating adhesive.

COVE-MATE is a solvent-free, quick grab, interior coving and decorating adhesive. It replaces mechanical fixings in a multitude of home improvement applications. Dries to a white finish and can be over painted once dry.

Uses

Bond It **COVE-MATE** is ideal for fixing polystyrene and PU covings, skirting boards, architraves and dado rails, etc. It can be used internally on plaster, brick and stone. It is also suitable for bonding work tops to base units and for bonding cork tiles and cork sheet.

Preparation

Ensure all surfaces to be bonded are clean, dry and free from grease, dust or any other contaminants that may hinder adhesion.

Application

Carefully cut the tip off cartridge. Cut nozzle to required width of bead at a 45° angle and attach to cartridge. Place cartridge in a standard sealant gun.

For lightweight items (eg. coving, dado rails and skirting) apply the adhesive to the back of the item in one or two continuous 6mm beads and press immediately into place.

For bonding heavy items (eg. plasterboards, work tops and wall panels) apply the adhesive all the way around approx 30-50mm from the edge. Apply adhesive direct to battens also and then press the item in to place. Note: with heavy items we recommend providing temporary support until the adhesive has dried.

Clean any excess material with a damp cloth. Full bond strength will be achieved 24-48 hours after application.

Limitations

- At least one of the surfaces must be porous.
- Not suitable for polythene, polypropylene, Teflon or nylon.
- On low porosity surfaces or in damp, cold or humid conditions, curing time may be significantly affected.
- Only apply between 5°C and 30°C.
- Not recommended for plaster coving.

Container Size

EU3 plastic cartridge.

Shelf Life

Use within 2 years from date of manufacture. Store in unopened cartridges.

Storage Conditions

Store in cool, dry conditions and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Specification Summary

Flammability	Non flammable
Application Temperature	5°C to 30°C

Container Sizes:

Code:	BDCMWH
Size:	EU3
Colour:	White
Barcode:	5060021364678

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 3/3/16
Supersedes V1 30/5/07