



Never compromise on quality!



PC200 INHIBITOR

High Performance System Inhibitor



PLUMBERS COMPLETE RANGE

Description:

A chemical blend which inhibits corrosion, scale formation, hydrogen gassing and microbiological growth and boiler noise, presented in a cartridge for easy dosing of closed systems.

Uses

PC200 INHIBITOR is suitable for all metals and plastics in use with domestic central heating systems.

Application

Filling the system: Release the pressure then isolate a convenient radiator. Remove the air bleed screw and connect the **PC200** plastic adaptor in place of the bleed screw. Place the **PC200** cartridge in a sealant gun and holding the cartridge upright cut off the tip of the cartridge with a sharp knife. Connect the cartridge to the adaptor, open one of the isolation valves on the radiator and slowly inject the inhibitor into the radiator. When the cartridge is empty re-isolate the radiator. Remove the adaptor and replace the air bleed screw. Open the valves and repressurise the system.

Dosage: For maximum performance **PC200** should be dosed @ 0.3% i.e. 1 cartridge per 100L of water. Generally 1 cartridge contains enough concentrate for a typical system with a 14.5Kw Boiler (50,000 Btu/hr) domestic hot water tank and up to 10 radiators. Larger systems will require more pro rata. Overdosing will not cause any problems or detrimental affects to the system.

Please note: where a thermal storage appliance is fitted allowance must be made for the extra volume of primary water. The concentration can be checked with a conductivity metre.

Limitations

DO NOT ADD TO PRIMATIC SYSTEM.

Container Size

300ml plastic cartridge with special nozzle attachment for direct application.

Colour

Straw coloured paste.

Storage Conditions

Store in cool, dry conditions in tightly sealed container. Do not allow to freeze.

Shelf Life

3 years from date of manufacture when stored in original, unopened tubes.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Flashpoint	None
Appearance	Straw coloured thin paste
Odour	Aromatic
pH	7.5

Product Details:

Code:	BDPC200
Colour:	Straw
Size:	300ml
Barcode:	5060021367501



Part of the Bond It Plumbers Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
*Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com*



V2 27/07/12
Supercedes: V